

23409-P001US

PATENT

- 1 -



IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

In re Application of: Larry S. Pendell

Serial No.: 10/056,371

Filed: January 24, 2002

Group Art Unit: 2834

Before the Examiner: Not Yet Assigned

Title: INDUCTION GENERATOR SYSTEM AND METHOD

**PRELIMINARY AMENDMENT TRANSMITTAL LETTER**

Assistant Commissioner for Patents  
Washington, D. C. 20231

Sir:


Applicants transmit herewith a Preliminary Amendment, a Response to Notice of Omitted Items in a Nonprovisional Application and a copy of the Notice of Omitted Items in a Nonprovisional Application for the above-identified application.

- ☒ No additional fee is required.  
☐ The fee has been calculated as shown below:

---

**CERTIFICATION UNDER 37 C.F.R. § 1.8**

I hereby certify that this correspondence (along with any item referred to as being enclosed herewith) is being deposited with the United States Postal Service with sufficient postage as first class mail in an envelope addressed to the Assistant Commissioner for Patents, Washington, D.C. 20231, on March 27, 2002.

  
\_\_\_\_\_  
Signature

Serena Beller  
\_\_\_\_\_  
(Printed name of person certifying)

23409-P001US

PATENT

CLAIMS AS AMENDED						
	CLAIMS REMAINING AFTER AMENDMENT		HIGHEST NUMBER PREVIOUSLY PAID FOR	PRESENT EXTRA	SMALL ENTITY RATE	ADDITIONAL FEE
Total Claims:	16	-	20	0	x \$ 9 =	\$ 0.00
Independent Claims:	3	-	3	0	x \$42 =	\$ 0.00
TOTAL ADDITIONAL FEE FOR THIS AMENDMENT						= \$ 0.00

- ☐ Enclosed is a check in the amount of \$0.00.
- ☒ If the fee has been calculated incorrectly, the Assistant Commissioner is hereby authorized to charge any fee necessary for additional claims to Deposit Account No. 23-2426 (23409-P001US) in the name of Winstead Sechrest & Minick P.C. **A duplicate copy of this transmittal letter is enclosed.**

Respectfully submitted,

WINSTEAD SECHREST &amp; MINICK P.C.

Attorney for Applicants

By: Richard F. Frankeny  
 Richard F. Frankeny  
 Reg. No. 47,573

5400 Renaissance Tower  
 1201 Elm Street  
 Dallas, Texas 75270  
 (512) 370-2872

AUSTIN\_1\186519\1  
 23409-P001US - 03/27/2002

23409-P001US

PATENT



- 1 -

## IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

In re Application of: Larry S. Pendell

Serial No.: 10/056,371

Filed: January 24, 2002

Group Art Unit: 2834

Before the Examiner: Not Yet Assigned

Title: INDUCTION GENERATOR SYSTEM AND METHOD

**PRELIMINARY AMENDMENT**Assistant Commissioner for Patents  
Washington, D. C. 20231

Dear Sir:

Please consider the following Preliminary Amendment to the Specification in the above-identified application:

---

**CERTIFICATION UNDER 37 C.F.R. § 1.8**

I hereby certify that this correspondence (along with any item referred to as being enclosed herewith) is being deposited with the United States Postal Service with sufficient postage as first class mail in an envelope addressed to Assistant Commissioner for Patents, Washington, D.C. 20231, on March 26, 2002.

A handwritten signature in cursive script that reads "Serena Beller".

Signature

Serena Beller

(Printed name of person certifying)

23409-P001US

PATENT

IN THE SPECIFICATION

Please replace the paragraph beginning at page 7, line 17, with the following rewritten paragraph:

--FIGS. 2J and 2K are circuit diagrams of multiple magnetically coupled control windings according to the topology of FIG. 2H used in embodiments of the present invention to provide higher resolution of control;--

Please replace the paragraph beginning at page 8, line 19, with the following rewritten paragraph:

--FIGS. 3J and 3K are circuit diagrams of multiple magnetically coupled control windings according to the topology of FIG. 3H used in embodiments of the present invention to provide higher resolution of control;--

Please replace the paragraph beginning at page 9, line 14, with the following rewritten paragraph:

--FIGS. 4J and 4K are circuit diagrams of multiple magnetically coupled control windings according to the topology of FIG. 4H used in embodiments of the present invention to provide higher resolution of control;--

Please replace the paragraph beginning at page 10, line 10, with the following rewritten paragraph:

--FIGS. 6J and 6K are circuit diagrams of multiple magnetically coupled control windings according to the topology of FIG. 6H used in embodiments of the present invention to provide higher resolution of control;--

23409-P001US

PATENT

Please replace the paragraph beginning at page 29, line 4, with the following rewritten paragraph:

--The alternate circuit configurations FIG. 2M, FIG. 2N and FIG. 2P for the auxiliary windings of FIG. 2H are included to illustrate the varied ways that auxiliary control windings may be configured and still be within the scope of embodiments of the present invention. All the auxiliary control windings in FIGS. 1A-1L, FIGS. 2A-2K, FIGS. 3A-3K, FIGS. 4A-4K, and FIGS. 6A-6K, may be configured alternatively as was done in FIG. 2M, FIG. 2N and FIG. 2P for the auxiliary control winding 226 in FIG. 2H as additional embodiments of the present invention.--

Please replace the paragraph beginning at page 43, line 1, with the following rewritten paragraph:

--FIG. 7A is a block diagram of an induction generating system 780 employing a stand-alone self-excited induction generator 782, according to embodiments of the present invention, driving a variable electrical load 785. Self-excited induction generator 782 may employ any of the compatible auxiliary control windings and energy windings described in the embodiments of FIGS. 1A-1L, 2A-2K, 2M-2N, 2P, 3A-3K, 4A-4K and 6A-6K for auxiliary (AUX) windings 791 and three phase energy windings 798. The particular embodiment for energy windings 798 would depend on whether single phase or three phase energy windings were desired.--

Please replace the paragraph beginning at page 44, line 4, with the following rewritten paragraph:

--A prime mover engine 781 is used to supply rotational mechanical energy to induction generator 782 via a shaft 789. The induction generator 782 has three phase outputs 786, however other combinations of phase outputs (1 or 2 phase) are possible without departing from the scope of the present invention. Induction generator 782 employs a single energy winding that may be configured either as a three phase Wye

23409-P001US

PATENT

or Delta circuit. Likewise, induction generator 782 may employ one or more auxiliary control windings as described in the embodiments of FIGS. 1A-1L, 2A-2K, 2M-2N, 2P, 3A-3K, 4A-4K, 6A-6K. Feedback signals load voltage 786 and load current 787 represent the currents and voltages of phases 786 driving variable electrical load 785. Signals 787 and 788 are coupled to controller 784. Controller 784 couples signals to switch elements (e.g., 248, 258 and 268) via control inputs (e.g., CN1 247, CN2 257 and CN3 267) to control the auxiliary windings of induction generator 782 in response to changes that occur in variable load 785. Since controller 784 is electrical, it may operate on each electrical cycle of phase outputs 786. The engine control 783 is electro-mechanical and is slower to respond to changes in the voltage and current outputs (e.g., frequency, amplitude, phase, etc.) of induction generator 782. Depending on the characteristics of the variable electrical load 785, there are theoretical optimum capacitance values coupled to the auxiliary windings of induction generator 782 and control settings for engine 781. Induction generator 782 may be configured as described in FIGS 1A-1L, 3A-3K, and 6A-6K. Each of these configurations has a three phase energy winding and a three phase auxiliary winding.--

Please replace the paragraph beginning at page 44, line 26, with the following rewritten paragraph:

--Engine 781 is coupled to induction generator 782 with shaft 789. If the rotor of induction generator 782 has some residual magnetism, then simply starting engine 781 and bringing it up to speed will start the process of establishing flux by induction in auxiliary windings 791. Embodiments of the present invention may use circuits in controller 784 to "pulse" the auxiliary windings with energy to start the excitation of auxiliary winding 791 if the voltages on auxiliary winding 791 do not establish once induction generator 782 rotation has commenced. For a particular design of induction generator 782, there will be a rotation speed for engine 781 necessary to determine

23409-P001US

PATENT

the correct and desired frequency of the output on energy windings 786. Load switch 830 may keep the variable load 785 disconnected until induction generator 782 is brought up to an initial speed. Engine 781 may be started in a no load condition where variable load 785 is disconnected via load switch 830. Controller 784 may be designed to only begin controlling after the engine speed is within a range of its steady state value using an engine speed sense signal in signals 797. After the engine speed has stabilized, controller 784 would sense the current supplied to the load 785 and continually adjust the amount of auxiliary winding capacitance as a function of the load current 787 and load voltage 788. If one did not have a control winding corresponding to embodiments of the present invention, the induction generator may have to be sized so that the output voltage could be maintained strictly by controlling the speed of the engine 784 and a user may have to accept poor quality outputs 786 without optimization of auxiliary windings 791. Changing the capacitance on the auxiliary winding 791, according to embodiments of the present invention, optimizes the capacitance for a load 785 as it varies and thus the engine 781 is required to maintain a condition proportional to an optimized generator. Since the controller 784 electronically switches the capacitance quickly as the load changes, it optimizes the auxiliary (field) windings 791 so the engine 781 only has to change its speed based on a power requirement for a higher efficiency generator. The generator control loop, from outputs 786 through controller 784 (signals 788 and 787) and auxiliary windings 791 is a fast control loop, and the engine control loop from engine controller 783 to engine 781 is a slower control loop. The rotational inertia of the mechanical system ensures that the fast control loop can respond to a change in current and optimize the generator 782 for a changing load 785 before the engine 781 either has to speed up or slow down to maintain the voltage for the changed load power requirement. The engine controller 783 would receive a new RPM set point, in one embodiment of the present invention, based on changing conditions of the load 785 determined by analyzing load voltage 788 and load current 787 via generator controller 784 and

23409-P001US

PATENT

master controller 893. This is further described with respect to FIGS. 15 and 16. Generator 782 may also have a single phase output (single phase output 786) without departing from the scope of the system embodiment in FIG. 7A.--

Please replace the paragraph beginning at page 51, line 12, with the following rewritten paragraph:

--The induction system 800 employs an induction generator 806 which has two electrically and magnetically isolated energy windings 803 and 804 and an auxiliary windings 817 which are electrically isolated from both energy windings 803 and 804 but may be magnetically coupled to energy winding 804. The possible generator 806 embodiments are explained in the descriptions of FIGS. 3A-3K and 6A-6K. The induction generator 806 with the two isolated energy windings 803 and 804 along with an energy storage flywheel 814 allows multiple modes of operation which may be set by user inputs 918 to master controller 893. The modes of operation that are possible with system 800 are as follows:--

Please replace the paragraph beginning at page 54, line 5, with the following rewritten paragraph:

--The induction system 900 uses induction generator 906 which has two electrically and magnetically isolated energy windings 903 and 904 and auxiliary windings 917 which are electrically isolated from both energy windings but may be magnetically coupled to energy winding 904. The possible generator 906 embodiments are explained in the descriptions of FIGS. 3A-3K and 6A-6K. The induction generator 906 with the two isolated energy windings 903 and 904 along with an energy backup inverter 914 powered by a battery source 919 allows multiple modes of operation which may be set by user inputs 918 to master controller 893. The modes of operation that are possible with system 900 are as follows:--



23409-P001US

PATENT

Please replace the paragraph beginning at page 56, line 20, with the following rewritten paragraph:

--FIGS. 10A and 10B are circuit diagrams of analog and digital circuits which may be used according to embodiments of the present invention. FIG. 10A illustrates three phase energy winding 1007 which comprises branch energy windings 1009, 1008 and 1010. Loads 1004, 1005 and 1006 are coupled between terminals A11, B11 and C11 and node 1018 respectively. Three phase energy winding 1007 may be any one of the three phase winding configurations explained in embodiments of the present invention (e.g., FIGS. 1A-1L, 3A-3K and 6A-6K). Current transformer 1003 is an analog component that may be used to sense the load current through load 1004. Other sense elements may also be used (e.g., a series sense resistor or Hall effect devices). The output of current transformer 1003 is coupled to an isolation and conditioning amplifier 1020 which generates a voltage VIL 1001 which is proportional to the load current in load 1004. Likewise, conditioning amplifier 1021 is used to sense the load voltage across load 1004 and generate a voltage VVL 1002 which is proportional to the load voltage across load 1004. Other embodiments of the present invention may sense all three phase load currents and voltages in the case the loads are unequal, in which case further processing of all three signals may be done to determine an appropriate feedback response.--

#### REMARKS

Attached hereto is a marked-up version of the changes made to the specification and claims by the current amendment. The attached page is captioned **"Version with markings to show changes made."**

23409-P001US


PATENT

Respectfully submitted,

WINSTEAD SECHREST & MINICK P.C.

Attorneys for Applicant

By:



Richard F. Frankeny

Reg. No. 47,573

Kelly K. Kordzik

Reg. No. 36,571

5400 Renaissance Tower  
1201 Elm Street  
Dallas, Texas 75270-2199  
(512) 370-2872

23409-P001US

PATENT

**VERSION WITH MARKINGS TO SHOW CHANGES MADE****In the Specification:**

Paragraph beginning at line 17 of page 7 has been amended as follows:

FIGS. 2J and 2K [2L] are circuit diagrams of multiple magnetically coupled control windings according to the topology of FIG. 2H used in embodiments of the present invention to provide higher resolution of control;

Paragraph beginning at line 19 of page 8 has been amended as follows:

FIGS. 3J and 3K [3L] are circuit diagrams of multiple magnetically coupled control windings according to the topology of FIG. 3H used in embodiments of the present invention to provide higher resolution of control;

Paragraph beginning at line 14 of page 9 has been amended as follows:

FIGS. 4J and 4K [4L] are circuit diagrams of multiple magnetically coupled control windings according to the topology of FIG. 4H used in embodiments of the present invention to provide higher resolution of control;

Paragraph beginning at line 10 of page 10 has been amended as follows:

FIGS. 6J and 6K [6L] are circuit diagrams of multiple magnetically coupled control windings according to the topology of FIG. 6H used in embodiments of the present invention to provide higher resolution of control;

Paragraph beginning at line 4 of page 29 has been amended as follows:

The alternate circuit configurations FIG. 2M, FIG. 2N and FIG. 2P for the auxiliary windings of FIG. 2H are included to illustrate the varied ways that auxiliary control windings may be configured and still be within the scope of embodiments of the present invention. All the auxiliary control windings in FIGS. 1A-1L, FIGS. 2A-2K [2L], FIGS. 3A-3K [3L], FIGS. 4A-4K, [4L] and FIGS. 6A-6K [6L],

23409-P001US

PATENT

may be configured alternatively as was done in FIG. 2M, FIG. 2N and FIG. 2P for the auxiliary control winding 226 in FIG. 2H as additional embodiments of the present invention.

Paragraph beginning at line 1 of page 43 has been amended as follows:

FIG. 7A is a block diagram of an induction generating system 780 employing a stand-alone self-excited induction generator 782, according to embodiments of the present invention, driving a variable electrical load 785. Self-excited induction generator 782 may employ any of the compatible auxiliary control windings and energy windings described in the embodiments of FIGS. 1A-1L, 2A-2K [2L], 2M-2N, 2P, 3A-3K [3L], 4A-4K [4L] and 6A-6K [6L] for auxiliary (AUX) windings 791 and three phase energy windings 798. The particular embodiment for energy windings 798 would depend on whether single phase or three phase energy windings were desired.

Paragraph beginning at line 4 of page 44 has been amended as follows:

A prime mover engine 781 is used to supply rotational mechanical energy to induction generator 782 via a shaft 789. The induction generator 782 has three phase outputs 786, however other combinations of phase outputs (1 or 2 phase) are possible without departing from the scope of the present invention. Induction generator 782 employs a single energy winding that may be configured either as a three phase Wye or Delta circuit. Likewise, induction generator 782 may employ one or more auxiliary control windings as described in the embodiments of FIGS. 1A[1K]-1L, 2A-2K [-2L], 2M-2N, 2P, 3A-3K [-3L], 4A-4K [-4L], 6A-6K [-6L]. Feedback signals load voltage 786 and load current 787 represent the currents and voltages of phases 786 driving variable electrical load 785. Signals 787 and 788 are coupled to controller 784. Controller 784 couples signals to switch elements (e.g., 248, 258 and 268) via control inputs (e.g., CN1 247, CN2 257 and CN3 267) to control the auxiliary windings of induction generator 782 in response to changes that occur in

23409-P001US

PATENT

variable load 785. Since controller 784 is electrical, it may operate on each electrical cycle of phase outputs 786. The engine control 783 is electro-mechanical and is slower to respond to changes in the voltage and current outputs (e.g., frequency, amplitude, phase, etc.) of induction generator 782. Depending on the characteristics of the variable electrical load 785, there are theoretical optimum capacitance values coupled to the auxiliary windings of induction generator 782 and control settings for engine 781. Induction generator 782 may be configured as described in FIGS. 1A-1L, 3A-3K [3L], and 6A-6K [6L]. Each of these configurations has a three phase energy winding and a three phase auxiliary winding.

Paragraph beginning at line 26 of page 44 has been amended as follows:

Engine 781 is coupled to induction generator 782 with shaft 789. If the rotor of induction generator 782 has some residual magnetism, then simply starting engine 781 and bringing it up to speed will start the process of establishing flux by induction in auxiliary windings 791. Embodiments of the present invention may use circuits in controller 784 to "pulse" the auxiliary windings with energy to start the excitation of auxiliary winding 791 if the voltages on auxiliary winding 791 do not establish once induction generator 782 rotation has commenced. For a particular design of induction generator 782, there will be a rotation speed for engine 781 necessary to determine the correct and desired frequency of the output on energy windings 786. Load switch 830 may keep the variable load 785 disconnected until induction generator 782 is brought up to an initial speed. Engine 781 may be started in a no load condition where variable load 785 is disconnected via load switch 830. Controller 784 may be designed to only begin controlling after the engine speed is within a range of its steady state value using an engine speed sense signal in signals 797. After the engine speed has stabilized, controller 784 would sense the current supplied to the load 785 and continually adjust the amount of auxiliary winding capacitance as a function of the load current 787 and load voltage 788. If one did not have a control winding

23409-P001US

PATENT

corresponding to embodiments of the present invention, the induction generator may have to be sized so that the output voltage could be maintained strictly by controlling the speed of the engine 784 and a user may have to accept poor quality outputs 786 without optimization of auxiliary windings 791. Changing the capacitance on the auxiliary winding 791, according to embodiments of the present invention, optimizes the capacitance for a load 785 as it varies and thus the engine 781 is required to maintain a condition proportional to an optimized generator. Since the controller 784 electronically switches the capacitance quickly as the load changes, it optimizes the auxiliary (field) windings 791 so the engine 781 only has to change its speed based on a power requirement for a higher efficiency generator. The generator control loop, from outputs 786 through controller 784 (signals 788 and 787) and auxiliary windings 791 is a fast control loop, and the engine control loop from engine controller 783 to engine 781 is a slower control loop. The rotational inertia of the mechanical system ensures that the fast control loop can respond to a change in current and optimize the generator 782 for a changing load 785 before the engine 781 either has to speed up or slow down to maintain the voltage for the changed load power requirement. The engine controller 783 would receive a new RPM set point, in one embodiment of the present invention, based on changing conditions of the load 785 determined by analyzing load voltage 788 and load current 787 via generator controller 784 and master controller 893. This is further described with respect to FIGS. 15 and 16. Generator 782 may also have a single phase output (single phase output 786) [(e.g., embodiments of FIGS. 2A-2L and FIGS. 4A-4L)] without departing from the scope of the system embodiment in FIG. 7A.

23409-P001US

PATENT

Paragraph beginning at line 12 of page 51 has been amended as follows:

The induction system 800 employs an induction generator 806 which has two electrically and magnetically isolated energy windings 803 and 804 and an auxiliary windings 817 which are electrically isolated from both energy windings 803 and 804 but may be magnetically coupled to energy winding 804. The possible generator 806 embodiments are explained in the descriptions of FIGS. 3A-3K [3L] and 6A-6K [6L]. The induction generator 806 with the two isolated energy windings 803 and 804 along with an energy storage flywheel 814 allows multiple modes of operation which may be set by user inputs 918 to master controller 893. The modes of operation that are possible with system 800 are as follows:

Paragraph beginning at line 5 of page 54 has been amended as follows:

The induction system 900 uses induction generator 906 which has two electrically and magnetically isolated energy windings 903 and 904 and auxiliary windings 917 which are electrically isolated from both energy windings but may be magnetically coupled to energy winding 904. The possible generator 906 embodiments are explained in the descriptions of FIGS. 3A-3K [3L] and 6A-6K [6L]. The induction generator 906 with the two isolated energy windings 903 and 904 along with an energy backup inverter 914 powered by a battery source 919 allows multiple modes of operation which may be set by user inputs 918 to master controller 893. The modes of operation that are possible with system 900 are as follows:

Paragraph beginning at line 20 of page 56 has been amended as follows:

FIGS. 10A and 10B are circuit diagrams of analog and digital circuits which may be used according to embodiments of the present invention. FIG. 10A illustrates three phase energy winding 1007 which comprises branch energy windings 1009, 1008 and 1010. Loads 1004, 1005 and 1006 are coupled between terminals A11, B11 and C11 and node 1018 respectively. Three phase energy winding 1007 may be any one of the three phase winding configurations explained in embodiments of the

23409-P001US

PATENT

present invention (e.g., FIGS. 1A-1L, 3A-3K [3L] and 6A-6K [6L]). Current transformer 1003 is an analog component that may be used to sense the load current through load 1004. Other sense elements may also be used (e.g., a series sense resistor or Hall effect devices). The output of current transformer 1003 is coupled to an isolation and conditioning amplifier 1020 which generates a voltage VIL 1001 which is proportional to the load current in load 1004. Likewise, conditioning amplifier 1021 is used to sense the load voltage across load 1004 and generate a voltage VVL 1002 which is proportional to the load voltage across load 1004. Other embodiments of the present invention may sense all three phase load currents and voltages in the case the loads are unequal, in which case further processing of all three signals may be done to determine an appropriate feedback response.

AUSTIN\_1\185828\1  
23409-P001US -